

Certificate Of Analysis

TEL : 02-2004-3000
 FAX : 02-2004-3258
 Address : 182, Pyeongsin 2-ro, Daesan-eup, Seosan-si, Chungcheongnam-do, Korea

Product Name : XTeer ATF SP3 Issue Date :
 Lot No. : Inspector :

Test Items	Test Method	Specification	Result
Appearance	Visual	Clear Red	Clear Red
Viscosity Index	ASTM D 2270	Min. 120	179
Density (@15 °C, kg/m3)	ASTM D 1298	Report	0.843
Kinematic Viscosity (40°C, mm2/s)	ASTM D 445	Report	32.20
Kinematic Viscosity (100°C, mm2/s)	ASTM D 445	Min. 5.5	6.8
Pour Point(°C)	ASTM D 97	Max. -39	-51
Flash Point(°C)	ASTM D 92	Min. 170	177
Foam test(ml/ml) SEQ.1	ASTM D 892	Max. 100	20-0
Foam test(ml/ml) SEQ.2	ASTM D 892	Max. 100	20-0
Foam test(ml/ml) SEQ.3	ASTM D 892	Max. 100	20-0

I hereby certify that the above test results are correct and true in all aspects. ◦



Signed by : ◦ _____ ◦◦