

PRODUCT DATA SHEET

Lubricants – Industrial

Converging the best and the most optimal, with incomparable power, enhancing performance at an amazing rate, **HYUNDAI XTeer** created by Hyundai's built-up technology will open the new world of Industrial lubricants.

XTeer Grease HT 2

Description

XTeer Grease HT 2 is high performance lithium complex grease with special EP additive. It is suitable for general service, application needed EP anti-wear protection and high temperature condition. As it is manufactured by using high-refined base oils and various high performance additives, it provides outstanding lubrication for many applications subjected to excellent thermal stability, extreme pressure, oxidation stability, and anti-wear property.

Application

- ✧ All sorts of bearings operated under boundary lubrication regime.
- ✧ High temperature and EP suitable for a wide range of general-purpose lubrication application.(roller bearing).
- ✧ Wheel bearings of heavy duty wheel and chassis.

Application

- ✧ Excellent resistance for the shock (extreme pressure) loading
- ✧ Good thermal and oxidation stability
- ✧ Service temperature: -20°C ~ +150°C

Typical Properties



XTeer Grease HT 2		Test Method
Thickener	Lithium complex	
Worked Penetration (25°C)	280	ASTM D 217
Dropping Point (°C)	270	ASTM D 566
Extreme pressure(kgf)	200	ASTM D 2596
Service temp. (°C)	Min	-20
	Max	+150